

# Deionisers, stainless steel (V4A), mixed bed resin

High quality stainless steel ion exchanger (V4A) pressure resistant up to 10 bar. High quality and longevity, parts in stainless steel in contact with medium. Optimized water distribution.

Without conductivity meter. Please order separately.

Material: Stainless steel

Max. flow rate l/h	Max. pressure bar	For	Ø mm	Height mm	Dimensions (ØxH)	Weight kg	PK	Cat. No.
450	10	SG 2000 SK	230	410	230 x 410 mm	18	1	9.914 442
800	10	SG 2800 SK	230	570	230 x 570 mm	24	1	9.914 452
1000	10	SG 4500 SK	230	785	230 x 785 mm	34	1	9.914 437
1000	10	SG 6200 SK	230	1025	230 x 1,025 mm	48	1	9.914 432
1500	10	SG 7000 SK	360	660	360 x 660 mm	52	1	6.285 619
1500	10	SG 15000 SK	360	1111	360 x 1,111 mm	92	1	6.285 621
450	10	SG 2000 3/4"	230	410	230 x 410 mm	18	1	9.914 512
800	10	SG 2800 3/4"	230	570	230 x 570 mm	24	1	9.914 509
1000	10	SG 4500 3/4"	230	785	230 x 785 mm	34	1	9.914 506
1000	10	SG 6200 3/4"	230	1025	230 x 1,025 mm	48	1	9.914 587
2000	10	SG 7000 1 1/4"	360	660	360 x 660 mm	53	1	9.914 502
3000	10	SG 15000 1 1/4"	360	1111	360 x 1,111 mm	93	1	6.035 609

## Zubehör:

Connection cables for deioniser / Evoqua Water Technologies

## Alternativen:

Deionisers, stainless steel (V4A), empty cartridge, without resin / Evoqua Water Technologies